

The Nikko Stirling Speed Sight **FLASH 1x25** is designed for fast and accurate target sighting and shooting. The **FLASH 1x25** is supplied with a 5/8" (15mm) Weaver / Picatinny claw mount for mounting on any suitable base plus a High Rise Mount for AR or similar platforms. Please consult your gunsmith or firearms dealer for advice about the suitability of this sight to your requirements.

## DESCRIPTION

- |                         |  |
|-------------------------|--|
| 1 - Illumination Turret | 4 - Windage Adjustment                 |
| 2 - Battery Compartment | 5 - Elevation Adjustment               |
| 3 - Base Mount Screw    | 6 - Rubber Lens Protection (not shown) |



A rubber lens protection for the **FLASH 1x25** is always included.

Depending on country different accessories and dot sizes are delivered.

## MOUNTING

1. Attach the **FLASH 1x25** to the Weaver base rail and make sure the base sits solid on the base.
2. Check to see that the clamp is fully down and hooked around the outside of the base.
3. Press the **FLASH 1x25** down at your desired position and forward firmly tighten down the clamp screw with the supplied hex wrench.

## OPERATION

### Battery

To install / replace the battery, hold the illumination turret and turn the cover on top to open. Install a new battery and close the cover. Battery type: CR2032

### On / Off

The **FLASH 1x25** allow to set 11 illumination intensity levels for the dot brightness.

Turn turret from zero (off) to your desired illumination level. Turn off after use.

For longer storage remove battery from sight.

## ADJUSTMENTS

The **FLASH 1x25** features adjustable elevation and windage dials with 1 MOA clicks.

Before adjustments remove the cap of the turret and replace it after final adjustment.

**Note:** One click equals 1 MOA  
△ 3cm@100m (1,5cm@50m) △ 1inch@100yds (0,5inch@50yds)

Elevation adjustment - up/down; on the top of the sight.

Windage adjustment - left/right; on the left of the sight.

For further adjusting repeat above steps.

## SPECIFICATIONS

Dimensions L x W x H	71.5 x 45 x 47 mm
Magnification	1 x
Dot Size	3 MOA
Brightness Levels	11 Positions
Elevation Adjustment Range	75 MOA $\hat{=}$ 218cm@100m
Windage Adjustment Range	75 MOA $\hat{=}$ 218cm@100m
Lens	$\varnothing$ 25
Battery	CR2032
1 MOA Click	1,5cm@50m $\hat{=}$ 0,5 inch@50yds

All details are subject to alterations without notice

**LIFETIME WARRANTY**

[WWW.NIKKOSTIRLING.COM](http://WWW.NIKKOSTIRLING.COM)



## Instruction Manual **FLASH 1x25**



[WWW.NIKKOSTIRLING.COM](http://WWW.NIKKOSTIRLING.COM)