

The Nikko Stirling **PRO T4** is designed for fast and accurate target acquisition and precise shooting. For professional use on rifles, AR's, shotguns and pistols.

MOUNTING

Depending on country a Weaver / Picatinny mount is supplied. A wide selection of other mounts for handguns is available as well as adaptor plate to use Doctor standard mounts. Please consult your gunsmith for more information.

BATTERY

To install or replace the CR 2032 battery open gently the battery tray on the right side. Insert a battery with the (+) side upwards. Push the battery tray back until it is flush with the body. Please note the battery tray uses a small rubber o-ring seal that provides waterproofness. It is recommended to remove the battery if you store the sight.



ZERO IN

Adjustment on the **PRO T4** should be made only at an approved shooting range.

1. Unlock adjustment

First unlock the adjustments on the backside with the small Allen key. Turn the screw in the rear of the sight marked "Lock" in anti clockwise direction for 3 full turns.



2. Elevation (E) and Windage (W) adjustment

After unlocking the adjustments, insert the Allen key into the Allen screw on top on the sight for elevation and /or for windage on right side. The adjustments are marked in increments of 1 MOA. 1 MOA equals app. 1 inch@100 yards (3cm@100m). If zero in eg. a pistol at 20 yards each adjustment mark is 1/5th inch (6mm@20m).



3. Locking adjustment

Once you have made the required adjustments lock the adjustments before firing at an approved shooting range. Should further adjustments be required then repeat these three steps.

ON/OFF – BRIGHTNESS SETTINGS

Use the 2-way switch on the side. Press either push button 3 seconds to turn it on or off. The **PRO T4** offers 10 settings. To increase press \wedge and to fade down press \vee button. The **PRO T4** supports an automatic shut off after 4 hours of inactivity. After use it is recommend turn off the illumination to safe battery lifetime. The brightness of the dot turns back at the same position as turned off.



SMARTDOT ACTIVATION

The **PRO T4** features SmartDot Activation. This is an automatic sleeping mode of the illumination after 3 minutes without movement. As soon as the sight gets moved it turns back automatically to the last illumination setting.

LIFETIME WARRANTY

The sight is warranted with Nikko Stirling Lifetime Warranty unless varied by local laws (batteries excluded). For details on lifetime warranty and product registration please visit www.nikkostirling.com

SPECIFICATIONS

| Dot | Bright steps | Elevation | | Windage | | Lens (WxH) (mm) | Size (LxWxH) (mm) |
|------|--------------|-----------|------------|----------|------------|-----------------|-------------------|
| | | cm@ 100m | in@ 100yds | cm@ 100m | in@ 100yds | | |
| 4MOA | 10 | 364 | 130 | 225 | 80 | 25.76x 22.01 | 51x28x33 |

All details are subject to alterations without notice.



Instruction Manual PRO T4



WWW.NIKKOSTIRLING.COM

WWW.NIKKOSTIRLING.COM